



Dimensions:

- A = 12' (144")
- B = 22' 3" (267")
- C = 5' 10" (70")
- D = 8' (96")
- E = 52" Top of Bed
- F = 6.5 Degree Load Angle

Loads:

- 4400 lbs Payload
- 2794 lbs Trailer Weight
- 501 lbs Hitch Empty Weight
- 1150 lbs Hitch Fully Loaded Weight
- 7194 lbs GVWR
- One (1), 6000 lb Axle

Specifications and Features *(Base Trailer)*

Ground to Travel to Dock Height	DOT Lights & Reflectors	16 x 6, 8 Bolt Modular Wheels
2-5/16" Ball Hitch	Grade 55 - 3/16" Diamond Plate Flooring	12" x 2" Electric Brakes
4" Frame Depth	Fold Down Transport Locks	Tie Downs (4)
LT235/85R16E Tire Size	Hydraulic Safety Valves	Rear Platform Support Jacks
36" Tailgate Ramp	Single Pin Grounded +12 VDC Power Cable	Breakaway Kit with Chains
DC Electric /Hydraulic Pump	Blue with White Trim Standard	Tongue Jack

Options

Steel Sides (12")LALP9201	5/8" Tie Down Rail..... LALP9215	Hydraulic Pump Cover..... LALP3161
40" Fence Pkg..... LALP9206	Spare Tire Carrier..... LALP1147	2 -1/2" Pintle Hitch..... LALP4347
Xtra Bed Lgth p/ftLALP9231	Spare Tire w/ Wheel..... 600P6599	Tailgate Winch (Hand)..... LALP9221
Xtra Bed Wdth 6".....LALP9236	Cargo Winch 3300#..... LALP4412	Special Paint Color LALP9226
Xtra Tie Downs.....LALP9211	Aux. Battery Hldr LALP3024	(Machinery Enamel Only)
	(Battery not included)	

Items for Tow Vehicle *(Installation not Included)*

2-5/16" High Rise Ball	600P6203	Brake Controller.....	600P6221
Pump Power Cable	LALP4351		