



Dimensions:

- A = 8' 6" (102")
- B = 16' 3" (195")
- C = 6' 2" (74")
- D = 11' 4" (136")
- E = 5 Degree Load Angle
- Clearance of deck at transport height = 11.5"

Loads:

- 300 lbs Tongue Load (Trailer)
- 650 lbs Tongue Load (Cargo)
- 950 lbs Total Tongue Load
- 825 lbs Wheel Load (Trailer)
- 2675 lbs Wheel Load (Cargo)
- 7950 lbs Total Wheel Load
- One (1), 7000 lb Axles

Specifications and Features (Base Trailer)

- Ground to Travel Height
- GVWR 7950 lbs
- Payload Maximum 6000 lbs
- Trailer Weight 1950 lbs
- 3.0 to 1 Payload to Trailer Weight Ratio
- Tires ST235/80R16LRE (3500 lbs Capacity Each)
- Cylinders 3" Diameter x 12" Stroke
- Hitchball 2-5/16" Diameter
- Ramp Built-in
- Lockable Storage Compartment
- Controlled Descent
- Tie Down Rail Built-in

- DC Electric/Hydraulic Pump
- Tongue Jack
- Four (4) "D" Rings
- Breakaway Kit with Chains
- Electric Brakes Both Axles
- LED Lighting with 7 Pin Connector
- Single Pin Grounded 12 VDC Power Cable
- Control Switch with Cable
- HSLA Steel Construction (No Angle or Channel Iron)
- Grade 55 - 3/16" Diamond Plate Flooring
- Combination Hydraulic/Rubber Suspension

Options

- On Board Power – Battery, Charger & Maintainer
- Cargo Winch 6000#
- Pintle Hitch (2-1/2" Lunette)

- Aluminum Wheels
- Spare Tire, Wheel & Carrier
- Special Paint (True Blue is Standard)